

(19) World Intellectual Property
Organization
International Bureau



529 660

(43) International Publication Date
15 April 2004 (15.04.2004)

PCT

(10) International Publication Number
WO 2004/032289 A1

(51) International Patent Classification⁷: H01R 13/635,
G06K 7/00, 13/08, H05K 5/02

(21) International Application Number:
PCT/US2003/031617

(22) International Filing Date: 3 October 2003 (03.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
290656/2002 3 October 2002 (03.10.2002) US

(71) Applicant (for all designated States except US): MOLEX
INCORPORATED [US/US]; 2222 Wellington Court,
Lisle, IL 60532 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MATSUKAWA,
Jun [JP/JP]; Court-pal Kobayashi 307, 12-15 Chuo-rinkan
3-chome, Yamato-shi, Kanagawa 242-0007 (JP).

TOMITA, Mitsuhiro [JP/JP]; 6-5-719 Nishi-tsuruma
3-chome, Yamato-shi, Kanagawa 242-0005 (JP). MAT-
SUMOTO, Yasuyoshi [JP/JP]; Heights-Ichikawa-Daisan
#305, 12-19 Chuo 6-Chome, Yamato-shi, Kanagawa
242-0021 (JP). YAMANE, Hiroshi [JP/JP]; ** (JP).


(74) Agent: CALDWELL, Stacey, E.; Molex Incorporated,
2222 Wellington Court, Lisle, IL 60532 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN,
YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: MEMORY CARD CONNECTOR



(57) **Abstract:** A memory card connector has an interior cavity into which a memory card is inserted to a temporary retained position and then to a fully inserted position. The connector includes a n insulating housing having a rear terminal-mounting section at a rear of the cavity. A plurality of terminals are mounted on the terminal-mounting section and have contact portions for engaging contacts on the memory card. A slider is movably mounted on the housing and is engageable with the memory card for movement therewith. The slider is slidable along a side wall of the housing. The slider has a projection engageable in a recess in a side of the memory card. A sheet metal shell covers at least a portion of he insulating housing and includes a cover plate overlying at least a portion of the cavity. A side wall plate depends from the cover plate and overlies at least a portion of the side wall of the housing. A spring structure is stamped and formed out of an opening in the side wall plate and is engageable with the slider to bias the projection of the slider into the recess in the memory card. The spring structure is integral with the side wall plate at opposite edges of the opening.